

KASSER I

M4 INDUSTRIES

Multirole MRAP Armoured Personnel Carrier



KASSER I



Multirole MRAP Armoured Personnel Carrier



GENERAL

- Crew – Driver, Commander, Gunner plus 6
- Gross Vehicle Mass – 11,450 kg
- Tare – 9,600 kg (unladen)
- Payload – 1,850 kg

DIMENSIONS

- Length – 6,160 mm
- Width – 2,420 mm
- Height – 2,600 mm
- Ground Clearance – 470 mm
- Wheel Base – 3,240 mm

KEY CHARACTERISTICS

- Engine – Cummins 5.9 TC / Euro III
- Power – 171 Kw (230 Hp) @ 1,500 rpm
- Torque – 800 Nm @ 1,800 rpm
- Power / Weight – 20
- Max Speed – 110 km/h
- Road Range – 800 km @ 80 km/h
- Transmission – Allison 2500
- Axles – Axle Tech Rigid Axles
- Tyres – Michelin 365/80 R20 with RFls
- Suspension – Parabolic with Shock Absorbers
- Turning circle – 16.2 m Kerb to Kerb

PROTECTION

- Ballistic – B7+
- Landmine – Stanag Level 3B

STANDARD EQUIPMENT

- Central Tyre Inflation System
- Remote Weapon Station Interface
- Rear roof mounted rotating ring gear
- 11 x Gun Ports – Side and rear window
- 4 x Antenna Mountings
- Doors – 2 x front; 1 x rear
- Air-Conditioner 36 000 BTU (2 x 18 000 BTU)
- Fire Extinguisher in Cabin
- Storage Space – 2 Bins each side
- Interior Cabin Lights
- Draw Bar and Towing Interfaces
- Jack and Base Plate, Wheel spanners
- Tyre inflator with hose and tool kit
- Turret – Side Protection Plates
- Siren and Strobe Lights
- 4Way Integrated Intercom System with Headsets
- 18 000lb (9 Ton) Winch with Snatch Block
- 12V / 24V Power Socket
- 2 X Auxiliary Batteries

OPTIONAL EQUIPMENT

- RAAD I 14.5 mm Remote Weapon Station
- FeWas 120 12.7 mm Remote Weapon Station

